FECURITY CASSISCATION OF THE AGE	· D- Δ 20 ^F	5 141			
REPORT DOCUMENTATION PAGE				Form Approved OM8 No. 0704-0188	
1a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED	12011117	16 RESTRICTIVE	MARKINGS	•	
2a. SECURITY CLASSIFICATION AUTHORITY FE 2b. DECLASSIFICATION DOWNGRADING SCHEDU	3. DISTRIBUTION/AVAILABILITY OF REPORT UNLIMITED				
1. PERFORMING ORGANIZATION REPORT NUMBE	5. MONITORING ORGANIZATION REPORT NUMBER(S) AFOSR - TR - 89 - U 132				
6a. NAME OF PERFORMING ORGANIZATION MASSACHUSETTS INST OF TECH	6b. OFFICE SYMBOL (If applicable)	7a. NAME OF MONITORING ORGANIZATION AFOSR/NE			
6c. ADDRESS (City, State, and ZIP Code) DEPARTMENT OF ELECTRICAL ENG AND COMPUTER SCIENCES CAMBRIDGE, MASSACHUSETTS 02139		7b. ADDRESS (City, State, and ZIP Code) BUILDING 410 BOLLING AFB, DC 20332			
8a. NAME OF FUNDING / SPONSORING ORGANIZATION * AFOSR	8b. OFFICE SYMBOL (If applicable)	9 PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER			
8c. ADDRESS (City, State, and ZIP Code)	NE	AFOSR-86-0288 10 SOURCE OF FUNDING NUMBERS			
(SAME AS ABOVE)		PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO	WORK UNIT ACCESSION NO
		61102F	2917	A3	
11. TITLE (Include Security Classification) Thin-Film Optics for Signal P 12. PERSONAL AUTHOR(S) Cardinal Warde	rocessing Applic	cations			
13a. TYPE OF REPORT 13b. TIME CO	14. DATE OF REPORT (Year, Month, Day) 15. PAGE COUNT				
FINAL FROM OLSep86 TO 31 May 88		89 Jan 25 5			
16. SUPPLEMENTARY NOTATION					
17. COSATI CODES 18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)					
FIELD GROUP SU8-GROUP					

19. ABSTRACT (Continue on reverse if necessary and identify by block number)

High-resolution, high-speed, spatial light modulators that offer excellent spatial uniformity are the key devices impeding progress in the areas of optical information processing and computing. The thrust of the MIT research effort is in the area of material, devices and systems for optical information processing. Our research is focused on (1) the growth, processing and characterization of optical crystals for spatial light modulation, (2) spatial light modulator prototype device development and (3) applications of spatial light modulators in symbolic optical processors. This final report describes the purchase assembly and operation of a RF sputtering system that is supporting a number of these and other DOD sponsored research programs at MIT.

ams at MIT.

Appendix STATEMENT A.

Appendix

20. DISTRIBUTION / AVAILABILITY OF ABSTRACT	21 ABSTRACT SECURITY CLASSIFICATION
☐ UNCLASSIFIED/UNLIMITED ☐ SAME AS RPT ☐ DTIC USERS	UNCLACCIFIED
22a. NAME OF RESPONSIBLE INDIVIDUAL	226 TELEPHONE (Include Area Code) 22c. OFFICE SYMBOL
GILES	(202) 767-4931

THIN-FILM OPTICS FOR SIGNAL PROCESSING APPLICATIONS

Final Report AFOSR-86-0288 January 25, 1989

Cardinal Warde

Department of Electrical Engineering and Computer Science
Massachusetts Institute of Technology
Cambridge, MA 02139, USA

AIR FORCE OFFICE OF SCIENTIFIC RESEARCH Bolling Air Force Base, D.C. 20332

THIN FILM OPTICS FOR SIGNAL PROCESSING APPLICATIONS

INTRODUCTION

High-resolution, high-speed, spatial light modulators that offer excellent spatial uniformity are the key devices impeding progress in the areas of optical information processing and computing. The thrust of the research effort is in the area of materials, devices and systems for optical information processing. Our research is focused on (1) the growth, processing and characterization of optical crystals for spatial modulation, (2) spatial light modulator prototype device development and (3) applications of spatial light modulators in symbolic optical processors.

This final report describes the purchase, assembly and operation of a RF sputtering system that is supporting a number of these and other DOD sponsored research programs at MIT.


SPUTTERING SYSTEM PURCHASED

The sputtering system purchased under this grant was built around a MRC 8667 chassis. Before purchasing the MRC 8667 system, we investigated several other competitive models. In particular, serious consideration was given to:

- (1) CVC Model 2800 system
- (2) Edwards E610 system

Because several of our users require three-target co-sputtering, the basic sputtering unit had to accommodate three guns, and had to be readily modifiable. After careful examination of all three models, we found that the MRC 8667 system would require the least work to achieve the necessary modifications. Furthermore, MRC gave us the best discount on the price.

The major components that constitute the sputtering system were, therefore, purchased from Materials Research Corporation. These were tested and assembled to fabricate the sputtering system. Some of the items were bought



used to stay within budget limitations. The major components of the system are listed below:

- 1. Basic 8667 Module (Model No. 10-8667-0200)
- 2. Five Inch RF Diode Cathode Assembly (Model No. 10-894-99-004)
- 3. 2 BA(VHS-6-Diff) Vacuum Station W/M.P.Auto pumpdown (Model No. 10-894-99-035)
- 4. Used 1.5 kW RF Supply
- 5. Used 2400 liter/sec. Diffusion Pump
- 6. Used Liquid Nitrogen Trap
- 7. Used Throttle Valve

The mechanical pump on the system was purchased under a different contract. A diagram of the control panel of the sputtering system is shown in Fig. 1.




Fig. 1. Control Panel of Sputtering System

BENEFITS OF THE SPUTTERING SYSTEM

Some of the DOD-sponsored programs that are currently being supported by the new sputtering system are listed below:

Sponsor:

DARPA through RADC, Hanscom AFB

Contract No.:

F19628-85-K-0050

Thrust of Research:

Crystal growth, post-growth processing and characterization of the optical, electronic electrooptic and photorefractive properties of doped BaTiO₃ crystals. Research involves similar characterization studies on Bi₁₂SiO₂₀, Sr_XBa_{1-X}Nb₂O₆

and LiNbO 2.

Sponsor:

DARPA through AFOSR

Grant No.:

AFOSR-86-0301

Thrust of Research:

Experimental and theoretical investigation of hybrid symbolic optical processing machines for logical inference. Experimental work involves the use of electrically and optically-addressed spatial light modulators to code and manipulate patterns representing the knowledge base, rules, and queries.

Sponsor:

RADC/Hanscom AFB

Contract No.:

F19628-87-C-0173

Thrust of Research:

This program is concerned with the optimization of BaTiO₃ crystals for optical computing applications, and it involves the delivery of doped and undoped samples of photorefractive BaTiO₃ to Hanscom Air Force

Base.

In addition to the programs listed above, there are two other groups within the MIT Crystal Physics Laboratory, who are also involved in insulating oxide crystal growth and characterization that will also be using the sputtering system. These groups are led by Dr. Hans Jenssen and Prof. Harry Tuller.

The above programs all rely on the sputtering machine for: (1) the sputter-deposition of thin transparent conductive electrodes of indium-tin-oxide on $BaTiO_3$, $LiTaO_3$, $Bi_{12}SiO_{20}$, $Sr_XBa_{1-X}Nb_2O_6$ and microchannel plates, and/or (2) the sputter-deposition of insulating layers of materials, such as, SiO and SiO₂.

The acquisition of the requested sputtering now permits us to determine the deposition conditions that are most compatible with each of the above electrooptic and photorefractive materials. Because of the widely varying properties of these materials, and the special handling that is often required the coating of these materials was hitherto not reproducible.

We believe that the in-house quality control that we are now achieving with this sputtering system will considerably improve the chances for significant advances in spatial light modulator technology and optical signal processing research.